

End Caps - BOX Refrigerated Self-Service Case 32"D

DIMENSIONS / SHIPPING				
Model	L"	L1"	L2"	Est Wt (lbs)
B3632	N/A	36.625	3.125	N/A
B4732	N/A	47.625	3.125	N/A
B5932	N/A	59.625	3.125	N/A
B7132	N/A	71.625	3.125	N/A
B8832	N/A	88.375	3.125	N/A

ELECTRICAL															
Model	System Circuit Volts			Ph	Frq	Rated Load Amps	Min Cir Amps	Max OCP Amps	Watts	Wires	NEMA Plug	Amps Lights	Amps Fans	Amps Anti-Sweats	Amps Misc/Refrig/Heat
B3632	Remote(R404A)-Type II Env	Circuit #1	110-120	1	60	1.13	15	15	99	2+G	Leads Multiple	0.83	0.30		N/A
	Remote(R404A)-Type I Env	Circuit #1	110-120	1	60	1.13	15	15	99	2+G	Leads Multiple	0.83	0.30		N/A
	Remote(GLYCOL)	Circuit #1	110-120	1	60	1.13	15	15	99	2+G	Leads Multiple	0.83	0.30		N/A
	Self-Contained-Type II Env	Circuit #1	110-120	1	60	16.00	20	20	1,371	2+G	5-20P or L5-20P	0.70	0.96	4.10	10.50
B4732	Remote(DX)-Type II Env	Circuit #1	110-120	1	60	1.47	15	15	139	2+G	Leads Multiple	1.17	0.30		N/A
	Remote(DX)-Type I Env	Circuit #1	110-120	1	60	1.47	15	15	139	2+G	Leads Multiple	1.17	0.30		N/A
	Self-Contained-Type II Env	Circuit #1	208-240	1	60	9.55	20	20	1,750	2+G	6-20P or L6-20P	0.36	0.86	2.23	6.10
B5932	Remote(DX)-Type I Env	Circuit #1	110-120	1	60	2.12	15	15	188	2+G	Leads Multiple	1.52	0.60		N/A
	Remote(DX)-Type II Env	Circuit #1	110-120	1	60	2.12	15	15	188	2+G	Leads Multiple	1.52	0.60		N/A
	Remote(GLYCOL)	C O N T A C T F A C T O R Y F O R U P D A T E D I N F O R M A T I O N													
B7132	Self-Contained-Type II Env	Circuit #1	208-240	1	60	11.49	20	20	2,124	2+G	6-20P or L6-20P	0.36	1.16	2.27	7.70
	Remote(DX)-Type II Env	Circuit #1	110-120	1	60	2.36	15	15	238	2+G	Leads Multiple	1.68	0.60		0.08
	Remote(DX)-Type I Env	Circuit #1	110-120	1	60	2.36	15	15	238	2+G	Leads Multiple	1.68	0.60		0.08
B8832	Self-Contained-Type II Env	Circuit #1	208-240	1	60	15.31	20	20	2,901	2+G	6-20P or L6-20P	0.36	1.16	3.54	10.25
	Remote(R404A)-Type II Env	Circuit #1	110-120	1	60	3.13	15	15	306	2+G	Leads Multiple	1.93	1.20		N/A
	Remote(R404A)-Type I Env	Circuit #1	110-120	1	60	3.13	15	15	306	2+G	Leads Multiple	1.93	1.20		N/A
	Self-Contained-Type II Env	Circuit #1	208-240	1	60	20.41	30	30	2,901	2+G	6-30P or L6-30P	0.72	2.04	3.55	14.10

REFRIGERATION														
Model	Zone	Section	System	Envt	REMOTE REFRIGERATION					GLYCOL / R744 REFRIGERATION				
					SST (°F)	Conv. Rack BTUH	Para. Rack BTUH	Defrost Interval (Hrs)	Defrost Duration (Mins)	Total GPM	Pressure Drop (psi)	Concent (%)	Liquid Temp (°F)	
B3632	All	Main	Remote-R404A-Type II Env	Type II	20	4,320	4,000	4.00	25.00	N/A	N/A	N/A	N/A	
	All	Main	Remote-R404A-Type I Env	Type I	20	3,542	3,280	4.00	25.00	N/A	N/A	N/A	N/A	
	All	Main	Remote-Glycol	Type II	N/A	4,320	4,000	4.00	25.00	1.50	2.58	35%	20.00	
	All	Refrigerator	Self-Contained-R449A-Type II Env	Type II	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
B4732	All	Main	Remote-DX-Type II Env	Type II	20	5,918	5,480	4.00	25.00	N/A	N/A	N/A	N/A	
	All	Main	Remote-DX-Type I Env	Type I	20	4,882	4,520	4.00	25.00	N/A	N/A	N/A	N/A	
	All	Refrigerator	Self-Contained-R449A-Type II Env	Type II	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
B5932	All	Main	Remote-DX-Type I Env	Type I	20	5,746	5,320	4.00	25.00	N/A	N/A	N/A	N/A	
	All	Main	Remote-DX-Type II Env	Type II	20	7,042	6,520	4.00	25.00	N/A	N/A	N/A	N/A	
	All	Refrigerator	Self-Contained-R449A-Type II Env	Type II	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
B7132	C O N T A C T F A C T O R Y F O R U P D A T E D I N F O R M A T I O N													
	All	Main	Remote-DX-Type II Env	Type II	20	8,618	7,980	4.00	25.00	N/A	N/A	N/A	N/A	
	All	Main	Remote-DX-Type I Env	Type I	20	7,042	6,520	4.00	25.00	N/A	N/A	N/A	N/A	
B8832	All	Refrigerator	Self-Contained-R449A-Type II Env	Type II	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	All	Main	Remote-R404A-Type II Env	Type II	20	13,046	12,080	4.00	25.00	N/A	N/A	N/A	N/A	
	All	Main	Remote-R404A-Type I Env	Type I	20	10,606	9,820	4.00	25.00	N/A	N/A	N/A	N/A	
	All	Refrigerator	Self-Contained-R449A-Type II Env	Type I	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	

INTENDED ENVIRONMENT		
Type II - Designed to operate in ambient conditions of 80°F and 60% relative humidity unless noted otherwise under Envt above.		
WARMEST AVERAGE PRODUCT TEMP & INTENDED USE OF ZONES		
Zone	Temp (°F)	Intended Use
1	40	Packaged refrigerated products

IMPORTANT NOTES
1) ELECTRICAL NOTE: If GFCI is required, a GFCI breaker MUST be used in lieu of a GFCI receptacle
2) Performance issues from adverse conditions not covered by warranty.
3) Keep unit at least 15' from air curtain disruptions.
4) End panels must be tightly joined or 6" away from any structure to prevent condensation.
5) Do not expose unit to direct sunlight or any heat source.
6) Tile floors, low ceilings, or small rooms will increase noise level.



End Caps - BOX Refrigerated Self-Service Case 32"D

REGULATORY	
All Models	Accordance with AHRI Std 1200 ETL Listed to UL 471 ETL Listed to CAN/CSA 22.2 No. 120 ETL Sanitation to NSF 7



In Accordance with
AHRI Std 1200

NOTE: ALL DIMENSIONS APPROXIMATE



- ELECTRICAL JUNCTION BOX (SUPPLIED WITH 6" LEADS OR POWER CORD).
- LOCATION OF DRAIN TUBE FOR REMOTE REF. ONLY (SUPPLIED WITH 3/4" OR 1 1/2" PVC TUBE).

- REFRIGERATION LINE CONNECTION.
- REMOTE FLOOR SINK & UTILITIES ACCESS AREA.

- SELF-CONTAINED CASE SERVICE ACCESS AREA.
- DRY CASE SERVICE ACCESS AREA.

End Caps - BOX Refrigerated Self-Service Case 32"D

NOTE: ALL DIMENSIONS APPROXIMATE

-  ELECTRICAL JUNCTION BOX (SUPPLIED WITH 6" LEADS OR POWER CORD).
-  LOCATION OF DRAIN TUBE FOR REMOTE REF. ONLY (SUPPLIED WITH 3/4" OR 1 1/2" PVC TUBE).

-  REFRIGERATION LINE CONNECTION.
-  REMOTE FLOOR SINK & UTILITIES ACCESS AREA.

-  SELF-CONTAINED CASE SERVICE ACCESS AREA.
-  DRY CASE SERVICE ACCESS AREA.

